Hyper 212 RGB Black Edition





The legendary Hyper air cooler is back and better than before. The Hyper 212 RGB Black Edition offers better installation and great performance, easily one of the best air cooling solutions. The aluminum top cover and nickel plated jet black fins, give the Hyper 212 RGB Black Edition a premium aesthetic appeal. The sleek jet black not only makes it look great, but also increase cooling performance.

The Hyper 212 RGB Black Edition maintains the same cooling efficiency as the Hyper 212 EVO. The Direct Contact Technology, stacked fins and 4 heatpipes, reduces airflow resistance, reduces heat spots, and increase airflow to the heatsinks.



Features

Sleek Finishing - Anodized gun-metal black with blasted aluminum surface finish to the top cover for a more refined look

Precise Air Flow with Nickle Black - Stacked fin array ensures least airflow resistance which allows cooler air flow into the heatsink. The nickel plated jet black also enhances radiation cooling performance

Direct Contact Technology - 4 heatpipes with Exclusive Direct Contact Technology providing effective and excellent heat dissipation

The new SF120R RGB Fan - is certified to sync with Motherboard RGB software or controlled by our controller. The wide speed range can be fine-tuned for maximum cooling performance or silent operation.

RGB LED Controller - the wired RGB LED Controller allows for customizable colors and effects with just the touch of a button

Snap and Play – Intuitive fan bracket design makes upgrading and removing the fan a breeze

EAN code	4719512076170
UPC code	884102048661
Net weight (Kg)	0.87
Gross weight (Kg)	1.07
Carton dimension (L x W x H)	51.5 x 33.5 x 26.5 cm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20′	4800	48	N/A
40′	9600	48	N/A
40 HQ	10800	54	N/A

Specifications & Packing Information

Product Name		Hyper 212 RGB Black Edition		
Product Number		RR-212S-20PC-R1		
CPU socket*		Intel® LGA 2066/2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366		
		AMD AM4/ AM3+ / AM3 / AM2+ /AM2 / FM2+ / FM2 / FM1		
Dimensions (L x W x H)		120 x 79.6 x 158.8 mm (4.7 x 3.1 x 6.3 inch)		
Heat Sink Material		4 Heat Pipes / Aluminum Fins/ Direct Contact		
Fan	Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)		
	Quantity	1 PC		
	Speed	650 ~ 2000 RPM (PWM) ± 10%		
	Air Flow	59 CFM (Max)		
	Air Pressure	2.1 mmH ₂ O		
	MTTF	160,000 Hours		
	Noise Level	8 ~ 30 dBA		
	Power Connector	4-Pin (PWM)		
	Rated Voltage	12 VDC		
	Rated Current	0.16 A		
	Safety Current	0.37 A		
	Power Consumption	1.92 W		
Warranty		2 Years		
*For the	*For the latest CPU support information, please visit our website			

*For the latest CPU support information, please visit our website



Key Features



SLEEK FINISHING Anodized gun-metal black with blasted aluminum surface finish to the top cover for a more refined look



PRECISE AIR FLOW WITH NICKLE BLACK Stacked fin array ensures least airflow resistance which allows cooler air flow into the heatsink. The nickel plated jet black also enhances radiation cooling performance



DIRECT CONTACT TECHNOLOGY

4 heat pipes with exclusive Direct Contact Technology providing effective and excellent heat dissipation



THE NEW SF120R RGB FAN is certified to sync with Motherboard RGB software or controlled by our controller. The wide speed range can be fine-tuned for maximum cooling performance or silent operation





UNIVERSAL MOUNTING KITS DESIGN The improved universal bracket design ensures easy and worry free installation on all platforms

COME WITH C10L WIRED RGB LED CONTROLLER

allows you to easily customize your RGB devices with just the touch of a button