

# Product data sheet

Specifications



## APC Easy UPS On-Line SRV 3000VA 230V with Extended Runtime Battery Pack, Argentina

SRV3KIL-AR

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2400 W
Rated power in VA	3000 VA
Plug standard	IEC 60320 C20
Nb of power socket outlets	2 Argentinean
Cable length	1.52 m
Number of cables	1
Provided equipment	Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord 1 x DC cable User manual USB cable

### General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

### Physical

Colour	Black
Height	33.6 cm
Width	33.5 cm
Depth	42.5 cm
Net weight	45.9 kg

Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical

## Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	CE IRAM
Standards	EN/IEC 62040-1 EN/IEC 62040-2

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	72 V
Number of battery filled slots	0

<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	5.5 h
<b>Battery life</b>	3...5 year(s)
<b>Battery charger power</b>	350 W rated
<b>Battery option</b>	SRV72BP-9A 1 1878 VAh SRV72BP-9A 2 2817 VAh SRV72BP-9A 3 3756 VAh SRV72BP-9A 4 4695 VAh

## Communications & Management

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Control panel</b>	Multifunction LCD status and control console
<b>Free slots</b>	1

## Surge Protection and Filtering

<b>Surge energy rate</b>	600 J
--------------------------	-------

## Packing Units

<b>Package 1 Weight</b>	49.8 kg
<b>Package 1 Height</b>	46.5 cm
<b>Package 1 width</b>	56 cm
<b>Package 1 Length</b>	56.5 cm

## Offer Sustainability

<b>EU RoHS Directive</b>	Under investigation
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------